1.1.1.

DOSATec Solenoid diaphragm dosing pump **HCO**

Solenoid diaphragm dosing pump for the exact dosing of liquid media.



Product description:

- Capacity: 0-5 l/h
- Pressure range: 0-10 bar
- Pump head material: PVDF
- Seals material: Viton®, EPDM
- Diaphragm material: PTFE
- Power supply: 230 VAC
- Alternative power supply: 24 VAC, 24 VDC
- Manual pump head ventilation valve
- Suitable for wall mounting
- Manual adjustment of stroke frequency
- Available languages: DE, EN, FR

Areas of application:

 Dosing of small and medium fluid volumes (water treatment, process industry, acids, bases, flocculants, precipitants, ...).

Scope of supply:

 DOSATec HCO Solenoid diaphragm dosing pump, accessory set (foot valve, hose, injection valve), connection cable end open

Ordering data:

Type:	Dosing capacity:	Pressure range:	Max. stroke frequency:	Hose connection:	Item number:
	l/h	bar	1/min	mm	
HCO PVDF/Viton® (Dosing pump HCO with PVDF pump head and Viton® seals.)	1.0	10	160	4 x 6	40230003
	2.0				
	3.0				
	5.0	8			
HCO PVDF/EPDM (Dosing pump HCO with PVDF pump head and EPDM seals.)	1.0	10			40230053
	2.0				
	3.0				
	5.0	8			

Viton® is the registered trademark for DuPont Dow Elastomer.

Subject to technical modifications and printing errors. Images may vary slightly from actual product. 08.09.2018