## 1.1.1.

## **DOSA**Tec Solenoid-driven diaphragm dosing pump KMS RH



Solenoid-driven diaphragm dosing pump for precise dosing of liquid media. Version for high viscosity media between 100 and 8000 cPs available for the LPV version.

#### **Product description:**

- Capacity: 0 18 l/h
- Pressure range: 0 20 bar
- Pump head material: PVDF
  - option: PP, acrylic, stainless steel
- Seals material: Viton®, EPDM
- Diaphragm material: PTFE
- Power supply: 230 VAC
- Alternative power supply: 115 VAC (24 VAC, 12 VDC, 24 VDC available on request)
- Manual pump head venting
- Suitable for mounting on a base
- Manual stroke length adjustment 0/25 100 %
- Inputs:
  - Level control
  - External dosing start
- Direct redox control, 0 1000 mV
- Optional output for alarm output
- Modes:
  - Conversion of analogue input signals
  - Dosing of pre-set volumes
- Available languages: DE, EN, FR

### Areas of application:

Dosage of small and medium fluid volumes (water treatment, process industry, acids, bases, flocculants, precipitants, etc.)

### Scope of supply:

 DOSATec Solenoid-driven diaphragm dosing pump KMS RH, accessory set (foot valve, hose, hose thread, injection valve, level switch)

### Ordering data:

Model:	Dosing capacity:	Pressure range:	Max. stroke	Hose connection:	Item No:
	l/h	bar	frequency: 1/min	mm	
KMS RH PVDF/Viton® (KMS RH dosing pump with PVDF pump head and Viton® seals.)	1	5		Suction side:	3913446
	1	20			3913440
	2	18	PVC hose, 4 x 6 from 18   2 up, 6 x 8 Discharge side:	3913441	
	4	15		3913447	
	5	10		3913442	
	8	8		PVDF hose 4 x 6	3913452
	10	5		from 18   2 up, 6 x 8	3913443
	18	2			3913444

Viton® is a registered trademark of DuPont Dow Elastomer.

Subject to technical modifications and printing errors. Images may vary slightly from actual product. 14.04.2020



## Ordering data:

Model:	Dosing capacity:	Pressure range:	Max. stroke	Hose connection:	Item No:
	I/h	bar	frequency: 1/min	mm	
KMS RH PVDF/EPDM (KMS RH dosing pump with PVDF pump head and EPDM seals.)	1	3	Suction side: PVC hose, 4 x 6		3913465
	1	5			3913466
	1	20		3913460	
	2	18		from 18   2 up, 6 x 8	3913461
	4	15	180		3913467
	5	10	FYDF hose, 4 x 6 from 18   2 up, 6 x 8	3913462	
	8	8		3913472	
	10	5		3913463	
	18	2			3913464

# Options:

Model:	Item No:
	0010000
PP pump heads I and IA	8613008
PP pump heads L and LA	8713130
PP pump heads M and MA	8613003
Stainless steel AISI 316 pump head li	8913185
Stainless steel AISI 316 pump head Li*	8913160
Stainless steel AISI 316 pump head Mi*	8913165
Acrylic pump head I	8913030
Acrylic pump head L	8913130
Acrylic pump head M	8913135
Acrylic pump head LPV L up to 8000 cPs	8913310
Acrylic pump head LPV M up to 8000 cPs	8913311
PVDF hose for K, KA, KMS and KMSA pump series 4 x 6	8713075
PVDF hose for K, KA, KMS and KMSA pump series 6 x 8	8713080
External level/alarm contact NO/NC	9013522
*No accessories included.	
**Hose connection for acrylic pump head up to 8000 cPs: Discharge side 16 x 22, PVC hose; Suction side 8 x 12 PE hose; Foot valve r	made of stainless steel not

Surcharge for stainless steel dosing head (excl. accessories and hoses). Please specify the required thread (cylindrical, conical or NPT) in your order.

### Pump heads:

Model:	Dosing capacity:	Pressure range:	Pump head:
	I/h	bar	
KMS RH	1	5	I
	1	20	I
	2	18	L
	4	15	L
	5	10	L
	8	8	L
	10	5	L
	18	2	M

Subject to technical modifications and printing errors. Images may vary slightly from actual product. 14.04.2020