

1.1.1.

**DOSATec Peristaltic pump DOSAFlex pH-Rx**

Capacity range up to 3 l/h, including pH or Redox-Regulation.



**Product description:**

- LCD hermoplastic hose
- Self-priming
- integrated electronic controller for measuring and regulation of pH and Redox value (accessories will be needed: sensors, flow cell, filter)
- pH-range: 4 ... 9
- Rx (ORP) range: -300 to +900 mV
- Set Point adjustment
- Over alarm, indicates an overdose situation
- Level switch input
- Power supply: 230 V

**Areas of application:**

- Domestic, small swimming pools and wellness centres.

**Scope of supply:**

- **DOSATec** Peristaltic pump **DOSAFlex**, optional installation kit (see options)

**Ordering data:**

Type:	Dosing capacity: l/h	Pressure range: bar	Suction lift meter	Hose connection: mm	Item number:
<b>DOSAFlex ph-Rx</b>	1.5	1.5	1	4,0 x 7,0	40113405
	3.0	1.5			40113400
	2.0	2.0		4,8 x 9,6	40113410
	3.0	3.0			40113415

**Options:**

Type:	Item number:
Injection valve IVN ½", 4 x 6 mm, PVDF, Viton® (seals); foot valve, axial type ½" with filter and weight, 4 x 6 mm, PVDF; suction hose PVC, 4 x 6 mm; PE dosing hose, 4 x 6 mm	8988210
Injection valve IVN ½", 4 x 6 mm, PVDF, EPDM (seals); foot valve, axial type ½" with filter and weight, 4 x 6 mm, EPDM; suction hose PVC, 4 x 6 mm; PE dosing hose, 4 x 6 mm	8988220

**Spare parts:**

Type:	Dosing capacity:	Item number:
Replacement peristaltic hose for DOSATecFlex-ph/Rx	1,5 l/h against 1,5 bar; 3,0 l/h gegen 1,5 bar	90113200
Replacement peristaltic hose for DOSATecFlex-ph/Rx	2,0 l/h against 2,0 bar; 3,0 l/h gegen 3,0 bar	90113201

Viton® is the registered trademark for DuPont Dow Elastomer.