
	<h1>P10</h1>
indicator	Peracetic acid
Application	<p>All kinds of water treatment, also sea water Conductivity acids are tolerated. (e. g. bottle washing machine, CIP-plants) The membrane system is mechanical resistant. The membrane system is highly resistant to surfactants (tensides).</p>
Measuring system	Membrane covered, amperometric 2-electrode system
Electronic	<p>Analog version:</p> <ul style="list-style-type: none"> - voltage output - not galvanically isolated electronics - analog internal data processing - output signal: analog (analog-out/analog) <p>Digital version:</p> <ul style="list-style-type: none"> - electronic is completely galvanically isolated - digital internal data processing - output signal: analog (analog-out/digital) or digital (digital-out/digital) <p>mA-version:</p> <ul style="list-style-type: none"> - current output analog - not galvanically isolated electronics - output signal: analog (analog-out/analog)
Information about the measuring range of sensors with 4-20 mA	<p>Slope of a sensor can vary production-related or application-related between 65% and 150% of the nominal slope</p> <p>-> Recommendation to determine the suitable measuring range or the suitable sensor: Concentration to be measured x factor 1.5 = measuring range of the sensor</p> <p>Example: Concentration to be measured 1.6 ppm x 1.5 = 2.4 -> recommended sensor with a measuring range of 5 ppm</p>
Working temperature	<p>Measuring water temperature: 0 ... +45 °C (no ice crystals in the measuring water)</p> <p>Ambient temperature: 0 ... +55 °C</p>
Temperature compensation	<p>Automatically, by an integrated temperature sensor sudden temperature changes must be avoided Response time t_{90} = approx. 8 min.</p>
Max. allowed working pressure	<p>Operation without retaining ring: 0.5 bar, no pressure impulses and/or vibrations</p> <p>Operation with retaining ring: 1.0 bar, no pressure impulses and/or vibrations</p>
Flow rate	approx. 15-30L/h in DF, small flow rate dependence is given
pH-range	pH 1 – pH 6




P10

Run-in time	P10H: First start-up approx. 3 h P10N: First start-up approx. 1 h P10L: First start-up approx. 30 min.
Response time	T ₉₀ : approx. 5 min. at 10 °C T ₉₀ : approx. 1.5 min. at 45 °C
Zero point adjustment	Not necessary
Slope calibration	At the device, by analytical determination
interferences	O ₃ : factor 2500 ClO ₂ : factor 1 H ₂ O ₂ : very low influence on the measuring value (reduce of the PAA-signal)
influence of conductivity acids	1 % sulfuric acid, 1 % nitric acid or 1 % phosphoric acid in the water have no influence to the measuring behaviour
Absence of the disinfectant	Max. 24 h
Connection	analog-out/analog version: 4-pole plug adapter analog-out/digital version: 4-pole plug adapter digital-out/digital version: 5-pole M12, plug-on flange 4-20 mA version: 2-pole terminal or 5-pole M12, plug-on flange
material	PVC-U, stainless steel 1.4571
Size	diameter: approx. 25 mm Length: analog-out/analog version approx. 175 mm analog-out/digital version approx. 195 mm digital-out/digital version approx. 205 mm 4-20 mA version approx. 220 mm (2-pole-terminal) approx. 190 mm (5-pole-M12)
Transport	+5 ... +50 °C (Sensor, electrolyte, membrane cap)
storage	Sensor: dry and without electrolyte no limit at +5 ... +40 °C
	Electrolyte: in original bottle protected from sunlight at +5 ... +35 °C min. 1 year or until specified EXP-Date
	Membrane cap: in original packing no limit at +5 ... +40 °C (used membrane caps can not be stored)
maintenance	Regular control of the measuring signal, min. once a week The following specifications depend on the water quality: Change of the membrane cap: once a year Change of the electrolyte: every 3 - 6 months
	EMC-Testing DIN EN 61326-1, 61326-2-3 RoHS compliant

Technical Data

1. P10 (Analog output, analog internal signal processing)
analog-out / analog


A potential-free electrical connection is necessary as the sensor electronic is not equipped with a galvanical isolation.

	Measuring range	resolution	Output Output resistance	Nominal slope	Voltage supply	Connection
P10H	0.5...200 ppm	0.1 ppm	0...-2000 mV 1 kΩ	-10 mV/ppm	±5 - ±15 VDC 10 mA	4-pole screw connector
P10N	5...2000 ppm	1 ppm		-1 mV/ppm		
P10L	0.005...2 % (20000 ppm)	0.001 % (10 ppm)		-1000mV/% (-0.1 mV/ppm)		
P10Up2000	5...2000	1 ppm	0...+2000 mV 1 kΩ	+1 mV/ppm	10 - 30 VDC	
P10Up5000	50...5000	1 ppm		+0.4 mV/ppm	10 mA	

(Subject to technical changes.)

2. P10 (analog output, digital internal signal processing)
analog-out / digital

- The power supply is galvanically isolated inside of the sensor.
- The output signal is galvanically isolated too, that means potential-free.


	Measuring range	Resolution	Output Output resistance	Nominal Slope	Power supply	Connection
P10H-An	0.5...200 ppm	0.1 ppm	analog 0...-2 V (max. -2.5 V) 1 kΩ	-10 mV/ppm	9-30 VDC approx. 56-20 mA	4-pole screw connector
P10N-An	5...2000 ppm	1 ppm		-1 mV/ppm		
P10L-An	0.005...2% (20000 ppm)	0.001% (10 ppm)		-1000 mV/% (-0.1 mV/ppm)		
P10H-Ap	0.5...200 ppm	0.1 ppm	analog 0...+2 V (max. +2.5 V) 1 kΩ	+10 mV/ppm		
P10N-Ap	5...2000 ppm	1 ppm		+1 mV/ppm		
P10L-Ap	0.005...2% (20000 ppm)	0.001% (10 ppm)		+1000 mV/% (+0.1 mV/ppm)		

(Subject to technical changes.)

3. P10 (digital output, digital internal signal processing)

digital-out / digital

- The power supply is galvanically isolated inside of the sensor.
- The output signal is galvanically isolated too, that means potential-free.

	Measuring range	Resolution	Output Output resistance	Power supply	Connection
P10H-M0c	0.5...200 ppm	0.1 ppm	Modbus RTU There are no terminating resistors in the sensor.	9-30 VDC approx. 56-20 mA	5-pole M12 connector
P10N-M0c	5...2000 ppm	1 ppm			
P10L-M0c	0.005...2% (20000 ppm)	0.001% (10 ppm)			


(Subject to technical changes.)

4. P10 4-20 mA (analog output, analog internal signal processing)

Analog-out / analog


A potential-free electrical connection is necessary as the sensor electronic is not equipped with a galvanical isolation.

4.1 Electrical connection: 2 pole terminal clamp

	Measuring range	resolution	Output Output resistance	Nominal slope	Voltage supply	Connection
P10MA-200	0.5...200 ppm	0.1 ppm	4...20 mA uncalibrated	0.08 mA/ppm	12...30 VDC $R_L = 50\Omega$ (12V) ... $R_L 900\Omega$ (30V)	2-pole terminal (2 x 1 mm ²) Recommended: Round cable Ø 4 mm 2 x 0.34 mm ²
P10MA-2000	5...2000 ppm	1 ppm		0.008 mA/ppm		
P10MA-5000	50...5000 ppm	1 ppm		0.0032 mA/ppm		
P10MA-2%	0.005...2 % (20000 ppm)	0.001 % (10 ppm)		8.0 mA/% (0.0008 mA/ppm)		
P10MA-5%	0.05...5 % (50000 ppm)	0.01 % (100 ppm)		3.2 mA/% (0.00032 mA/ppm)		

(Subject to technical changes.)

4.2 Electrical connection: 5 pole M12 plug-on flange

	Measuring range	resolution	Output Output resistance	Nominal slope	Voltage supply	Connection
P10MA-200-M12	0.5...200 ppm	0.1 ppm	4...20 mA uncalibrated	0.08 mA/ppm	12...30 VDC R _L = 50Ω (12V) ... R _L 900Ω (30V)	5-pole M12 plug-on flange Function of wires: PIN2: +U PIN3: -U
P10MA-2000-M12	5...2000 ppm	1 ppm		0.008 mA/ppm		
P10MA-5000-M12	50...5000 ppm	1 ppm		0.0032 mA/ppm		
P10MA-2%-M12	0.005...2 % (20000 ppm)	0.001 % (10 ppm)		8.0 mA/% (0.0008 mA/ppm)		
P10MA-5%-M12	0.05...5 % (50000 ppm)	0.01 % (100 ppm)		3.2 mA/% (0.00032 mA/ppm)		

(Subject to technical changes.)

Spare Parts

Type	Membrane cap	Electrolyte	Emery	O-ring
For all P10H	M10.1N with G-holder	EPS9H/W, 100 ml	S2	20 x 1.5 silicone
For all P10N				
P10Up2000				
P10Up5000		EPS9L/W, 100 ml		
For all P10L				
For all P10MA-200		EPS9H/W, 100 ml		
For all P10MA-2000				
For all P10MA-5000				
For all P10MA-2%		EPS9L/W, 100 ml		
For all P10MA-5%	M10G with G-holder	EPS7/W, 100 ml		

(Subject to technical changes.)

Slope of P9 and P10 versus pH

Temperature: 25°C / Flow rate: 30 l/h

